

IMAGEPROGRAF & IMAGEPROGRAF® IPF 755/750





TECHNICAL DOCUMENTS

LARGE-FORMAT PRINTING

image PROGRAF



SPECIFICATIONS

Print-Head

PF-04 Technology

FINE (Full-Photolithography Inkjet Nozzle Engineering) **Print Resolution (Max.**

2400 × 1200 dpi

Line Accuracy*
±0.1% or Less
Minimum Line Weight**

0.02mm

Number of Nozzles

Matte Black: 5,120 Nozzles

Other Colors: 2,560 Nozzles per Color

Droplet Size

4 Picoliter

Nozzle Pitch (Head Resolution)

1200 dpi × Two Rows

Print-Head Swath 1.07 inch

Ink Type

Cyan (C), Magenta (M), Yellow (Y), Black (K)

Pigment

Matte Black (MBK)

Ink Tank

PFI-102: MBK, C, Y, K

PFI-104: M

Ink Tank Capacity Starter: 90ml

Replacement: 130ml

Ink Supply Method

Tubing System with Sub-Tanks for Continuous

Ink Supply

Nozzle Recovery System Non-firing Nozzle Detection and Compensation

Printer Controller

L-COA Controller

Printer Memory

256MB

Hard Drive (iPF755 only) 80GB (SATA)

Mail Boxes (User Job Storage) (iPF755 only)

1 Common Inbox, 29 User Inboxes

(Password-protected)

Roll Feed

One Roll, Top-loading, Front Output

Cut Sheet

One Sheet, Top-loading, Front Output

Media Width Roll Feed

10" – 36" (254mm – 914mm)

Cut Sheet

8" – 36" (203.2mm – 914mm)

Printable Margins

Roll Feed

All Sides: 0.12" (3mm) or 0" for Borderless

Cut Sheet

Leading, Sides (Left and Right): 0.12" (3mm)

Trailing: 0.91" (23mm)

Maximum Print Length (Single Page)†

59' (18m)

Cut Sheet

63" (1.6m) **Borderless Printing Widths (Roll Media Only)**

10", B4, A3, 14", A2, 17", B2, A1, 24", B1, A0, 36"

Media Cutter

Durable Dual-blade Rotary Cutter

Media Thickness

0.07 - 0.8mm (2.8 - 31.4mil)

Media Core Sizes

2" and 3" Core (Adapter Included)

Maximum Roll Outer Diameter

5.9" (150mm)

Output Media Bin

Stackable Media Basket (Standard)

Output Media Bin Capacity

20 Sheets (With Stackable Configuration)

Printing Software

imagePROGRAF Printer Driver for Windows/Mac, HDI Driver^{††}, Printer Driver Extra Kit for Windows/ Mac (Free Layout, Color imageRUNNER® Enlargement Copy, Advanced Preview), Print Plug-in for Microsoft Word/Excel/PowerPoint for Windows, Digital Photo Front-Access for Windows, PosterArtist Lite for Windows

Operating System[†]

Windows 32-bit 2000/XP/ Server 2003/ Windows Vista®/Server 2008, Windows 64-bit XP/ Server 2003/Windows Vista/Server 2008 Macintosh OS X CUPS (10.4.9, 10.5.x) 32-bit, Macintosh OS X CUPS (10.5.x) 64-bit (Available in download only)

Print Language GARO, HP-GL/2, HP RTL

Interface

USB 2.0 Hi-Speed, 10/100/1000Base-T/TX

Protocol

TCP/IP (IPv4/IPv6), IPX/SPX, AppleTalk®, SNMP

(Canon MIB supported), HTTP

Acoustic Noise

Operation

50dB (A) or Less

Standby

35dB (A) or Less **Acoustic Power**

Approx. 6.6 Bels

Power Supply

AC 100-240V (50-60Hz)

Power Consumption

Maximum

140W or Less

Standby

5W or Less

Power Off

1W or Less (Executive Order Compliant)

Electrical Safety Regulations

UL® (USA), C-UL (Canada), S mark (Argentina), CE mark (EN60950, EN55022 classB, EN61000-3-2, EN-61000-3-3, EN55024) (EU), CB certification (Others)

Electromagnetic Interface RegulationsFCC Class B (USA), IC Class B (Canada)

Environmental Certifications

ENERGY STAR® (Worldwide), RoHS
Directive, WEEE, Executive Order (USA)

Operational Environment

Temperature

59 – 86 F° (15 – 30 C°)

Relative Humidity 10 - 80% (No Condensation)

Printer Dimensions (H × W × D) and Weight with Stand and Basket 41.8" × 51.3" × 34.3" (1,062mm × 1,304mm × 870mm)

Approx. 139 lb. (63kg)

Package Dimensions (H × W × D) and Weight•

Printer Main Package 30.3" × 56.5" × 32.7" (770mm × 1,434mm × 830mm)

Approx. 166 lb. (75kg)

Stand Package 9.4" × 55.1" × 30.7"

(1,585mm x 1,263mm x 2,348mm)

Approx. 38 lb. (17kg)

PosterArtist Roll Holder Set (RH2-33)

User-Replaceable Items
Ink Tank (PFI -102 MBK, C, Y, K; PFI-104 M)

Print-Head (PF-04)

Maintenance Cartridge (MC -10)

What's In The Box

Printer, User Software CD for Windows, User Software CD for Macintosh, User Manual CD, PosterArtist Lite CD, 6 Starter Ink Tanks (MBK×2, C, M, Y, K), 2" Core Media Spool with 3" Adapter, Print-Head PF-04, Maintenance Cartridge MC-10, Quick Setup Guide (Poster), Printer Reference Guide (Booklet), Power Cord, One-Year Onsite Limited Warranty, Registration Card, Stand, Stackable Media Basket, Accessory Box, Hardware (For Setting Up the Printer and Stand)

- Line accuracy repeatability is guaranteed after a user performs necessary adjustment and under the same environmental conditions. Applies to media for line drawing (Plain Paper, Coated Paper, CAD Translucent Matte Film, and CAD Tracing Paper) only.
- Theoretical value based on data resolution.
- The maximum printable length varies, depending on the application, OS, and RIP used.
- For AutoCAD or AutoCAD LT 2000/2000i/2002/2004/ 2005/2006/2007/2008/2009
- For imagePROGRAF Printer Driver. For printing from PostScript® applications such as Adobe Illustrator® or QuarkXPress™, please use a PostScript compatible RIP package. For a list of Canon recommended RIP packages, please consult with Canon Alliance and Industry Market program list of RIP vendors at www.usa.canon.com.
- The printer will be shipped on a pallet with stand box strapped on top of the main unit. Shipping dimensions and weight for iPF755/iPF750 are (H×W×D) 39.7" × 56.5" × 32.7", 205 lb.



Océ North America

Wide Format Printing Systems 5450 N. Cumberland Ave. Chicago, IL 60656

For more information, call us at 800-714-4427, email us.info@oce.com, or visit www.oceusa.com



©2010 Canon U.S.A., Inc. All rights reserved.

As an ENERGY STAR® Partner, Canon U.S.A., Inc. has determined that these products meet the ENERGY STAR guidelines for energy efficiency. ENERGY STAR and the ENERGY STAR mark are registered U.S. marks. Océ and the Océ logo are registered trademarks owned by Océ-Technologies B.V. CANON, IMAGEPROGRAF, IMAGERUNNER, and the GENUINE logo are registered trademarks of Canon Inc. in the United States and may also be registered trademarks or trademarks in other countries. IMAGEANYWARE is a trademark of Canon. All other referenced product names and marks are trademarks of their respective owners and are hereby acknowledged. Specifications and availability subject to change without notice.







